

UNIVERSITI TEKNOLOGI MARA

**ADSORPTION OF MERCURY FROM
SIMULATED FLUE GAS USING
ACTIVATED CARBON PRODUCED
FROM OIL PALM EMPTY FRUIT
BUNCH**

NOOR HIDAYU BINTI ABDUL RANI

Thesis submitted in fulfilment
of the requirements for the degree of
Master of Science

Faculty of Chemical Engineering

May 2015

CONFIRMATION BY PANEL OF EXAMINERS

I certify that a Panel of Examiners has met on 03rd December 2014 to conduct the final examination of Noor Hidayu Binti Abdul Rani on her Master of Science thesis entitled "Adsorption of Mercury from Simulated Flue Gas using Activated Carbon Produced from Oil Palm Empty Fruit Bunch" in accordance with Universiti Teknologi MARA Act 1976 (Akta 173). The Panel of Examiners recommends that the student be awarded the relevant degree. The panel of Examiners was as follows:

Siti Noor Suzila Maqsood-Ul-Haque, PhD
Senior Lecturer
Faculty of Chemical Engineering
Universiti Teknologi MARA
(Chairman)

Mohammad Asadullah, PhD
Professor
Faculty of Chemical Engineering
Universiti Teknologi MARA
(Internal Examiner)


Ridzuan Zakaria, PhD
Associate Professor
School of Chemical Engineering
Universiti Sains Malaysia (USM)
(External Examiner)

SITI HALIJJAH SHARIFF, PhD
Associate Professor
Dean
Institute of Graduates Studies
Universiti Teknologi MARA
Date: 15th May 2015

AUTHOR'S DECLARATION

I declare that the work in this thesis/dissertation was carried out in accordance with the regulations of Universiti Teknologi MARA. It is original and is the result of my own work, unless otherwise indicated or acknowledged as referenced work. This thesis has not been submitted to any other academic institution or non-academic institution for any degree or qualification.

I, hereby, acknowledge that I have been supplied with the Academic Rules and Regulations for Post Graduate, Universiti Teknologi MARA, regulating the conduct of my study and research.

| | | |
|----------------------|---|---|
| Name of Student | : | Noor Hidayu Binti Abdul Rani |
| Student I.D. No. | : | 2011747291 |
| Programme | : | Master of Science (Chemical Engineering) |
| Faculty | : | Chemical Engineering |
| Thesis Title | : | Adsorption of mercury from simulated flue gas using activated carbon produced from oil palm empty fruit bunch |
| Signature of Student | : |  |
| Date | : | May 2015 |

ABSTRACT

Mercury pollution is a global crisis facing society today because it is a toxic and hazardous element that can severely threaten human health and environment. Activated carbon as an effective adsorbent in capturing elemental mercury from flue gas was used for this research. In this research, activated carbon was produced from oil palm empty fruit bunch (EFB) using physical (steam) activation method and response surface methodology (RSM) is applied in order to maximize the BET surface area. One model has been developed for BET surface area and showed the activation temperature and activation time are the affecting factors for optimum activated carbon production. The optimum operating conditions were calculated using this model to produce activated carbon with relatively large BET surface area ($>500 \text{ m}^2/\text{g}$). Based on this optimum condition (765°C , 77 min), the experimental value of BET surface area obtained was $720.0 \text{ m}^2/\text{g}$, which is in agreement with that predicted from the model ($717.6 \text{ m}^2/\text{g}$). The activated carbon produced at optimum conditions was used as adsorbent for the mercury removal from simulated flue gas. The effect of flue gas temperature, inlet mercury concentration and types of activated carbon (modified AC and unmodified AC) were investigated throughout this work. Initially, activated carbon showed a good potential for adsorption of mercury at low temperature. However, as temperature increases from 90°C to 180°C , the efficiency of mercury removal decreased. When the inlet mercury concentration was increased, the mercury removal efficiency was increased. The effect of adsorption efficiency on surface modified activated carbon with potassium iodide (KI) was also studied and showed that the presence of I^- ion on the surface of activated carbon increased the percentage removal of up to 99% and concluded that 5 wt% of KI is deemed to be the maximum desirable loading.

ACKNOWLEDGEMENT

Alhamdulillah, all praise to Allah S.W.T, I have successfully completed my thesis on “Adsorption of mercury in simulated flue gas by using activated carbon from oil palm empty fruit bunch”. I am very grateful to Allah who gave me tremendous courage and spirit while facing the entire obstacle.

First of all, I wish to express my gratefulness to my project supervisor, Professor Dr. Sharifah Aishah Syed A. Kadir for her supervision, guidance and critiques towards this project. The discussions with Prof. were always been very insightful, and I will always be indebted to her for all the knowledge she shared with me. Her prompt responses and availability despite her constantly busy schedule were truly appreciated. Her encouragement and efforts led this project to successful completion in a timely fashion.

I also would like to thank my co-supervisor, Mrs. Sharmeela Matali for being a uniformly excellent advisor. She was always open-minded, helpful and provides me insightful suggestions, which have been greatly helpful to the advancement of my research. Thanks are also due to the Professor Masaki Takaoka for sharing all of his experience and helping me in this study.

My sincere appreciation also extends to all my colleagues, laboratory technicians and others who have provided assistance at various occasions. Their views and tips are useful indeed. I would also acknowledge Universiti Teknologi Mara (UiTM) for the funding for my thesis.

Last but not least, I take this opportunity to extend my deepest gratitude to my family for their unfailing love, unconditional sacrifice and moral support, which are far more than I could express in words.